

DPA500F

Ordering information


DP A 500 F -360

① ② ③ ④ ⑤



RoHS

- ① Series name
 ② Single output
 ③ Output wattage
 ④ Universal input
 ⑤ Output voltage



MODEL	DPA500F-360	
AC INPUT[V]	AC85 - 264	AC170 - 264
MAX OUTPUT WATTAGE[W]	500	750
DC OUTPUT VOLTAGE[V]	DC300 - 360	

SPECIFICATIONS

	MODEL	DPA500F-360	
INPUT	VOLTAGE[V]	AC100/120	AC200/240
	VOLTAGE RANGE[V]	AC85 - 170	AC170 - 264
	POWER FACTOR CORRECTION RANGE[V]	AC85 - 255	
	CURRENT[A]	5.6typ (ACIN 100V)	4.0typ (ACIN 200V)
	FREQUENCY[Hz]	47 - 63	
	APPARENT POWER[VA]	560typ (ACIN 100V)	800typ (ACIN 200V)
	INRUSH CURRENT[A]	15typ (ACIN 100V)	30typ (ACIN 200V)
	EFFICIENCY[%]	90typ (ACIN 100V)	95typ (ACIN 200V)
	POWER FACTOR	0.98typ (Complies with IEC61000-3-2)	
	LEAKAGE CURRENT[mA]	Less than 0.3	
OUTPUT	WATTAGE[W]	500	750
	VOLTAGE[V]	DC300 - 360 (Automatically changes according to input voltage)	
PROTECTION CIRCUIT AND OTHERS	OVERTOWRGE PROTECTION[V]	DC390 - 440	
	IOG	Inverter operation monitoring, Open-collector output, Maximum sink current 5mA, Maximum allowance voltage 35V	
	PR	Power-ready signal, Open-collector output, Maximum sink current 5mA, Maximum allowance voltage 35V	
	AUX	Auxiliary power supply for external signal, Output voltage:10 - 20V maximum, Output current:10mA	
	OTHERS	Inrush current protection, Parallel operation possible (Current balancing function), Thermal protection	
ISOLATION	INPUT-OUTPUT	Non isolated	
	INPUT-FG	AC3.000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)	
	OUTPUT-FG	AC3.000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature)	
ENVIRONMENT	OPERATING TEMP.,HUMID.AND ALTITUDE	*1 -20 to +85°C (Aluminum base plate), 20 - 95%RH (Non condensing) (Refer to DERATING CURVE), 3,000m (10,000feet) max	
	STORAGE TEMP.,HUMID.AND ALTITUDE	-40 to +85°C, 20 - 95%RH (Non condensing), 9,000m (30,000feet) max	
	VIBRATION	10 - 55Hz, 49.0m/s² (5G), 3minutes period, 60minutes each along X, Y and Z axis	
DPA	IMPACT	196.1m/s² (20G), 11ms, once each X, Y and Z axis	
SAFETY	AGENCY APPROVALS	UL60950-1, CSA C22.2 No.234, EN60950-1, EN50178 Complies with DEN-AN and IEC60950-1	
OTHERS	CASE SIZE/WEIGHT	58×12.7×130mm (W×H×D) / 150g max	
	COOLING METHOD	Conduction cooling (e.g. heat radiation from the aluminum base plate to the attached heat sink)	

*1 Please consult us in regard to use from -40°C.